

## C-clamps



- Clamping force of up to 15,000 N
- Nearly unbreakable and tempered
- Tried-and-true BESSEY all-steel quality



### C-clamp VC, stable

№	← a →		← b →		← x →	kN	kg	qty.	VB0002
	mm	"	mm	"	mm				
VC2	0 - 50	0 - 2	50	2	19.5 x 9.5	7	0,43	10	
VC3	0 - 75	0 - 3	50	2	22 x 10.5	13	0,63	10	
VC4	0 - 100	0 - 4	60	2 3/8	25 x 12	13	1,02	10	
VC6	0 - 150	0 - 6	75	3	27 x 13	15	1,41	10	
VC8	0 - 200	0 - 7 7/8	90	3 1/2	30 x 15	15	2,25	5	
VC10	0 - 250	0 - 10	100	4	40 x 20	15	4,01	5	



- Clamping force of up to 22,000 N
- Drop forged

### C-clamp SC

№	← a →		← b →		kN	kg	qty.	VB0002
	mm	"	mm	"				
SC40	0 - 40	0 - 1 5/8	40	1 5/8	5.5	0,40	10	
SC60	0 - 60	0 - 2 3/8	55	2 3/8	5.5	0,57	10	
SC80	0 - 80	0 - 3 1/8	65	2 9/16	10	0,99	10	
SC100	0 - 100	0 - 4	75	3	13.5	1,40	10	
SC120	0 - 120	0 - 7 7/8	85	3 1/4	18	2,10	10	
SC150	0 - 150	0 - 6	95	3 3/4	18	2,35	10	
SC200	0 - 200	0 - 7 7/8	105	4 1/4	22	4,00	5	



- Clamping force up to 20,000 N
- Drop forged, extremely stable

### C-clamp CDF

№	← a →		← b →		kN	kg	qty.	VB0002
	mm	"	mm	"				
CDF402	0 - 50	0 - 2	55	2	12	0,61	36	
CDF403	0 - 75	0 - 3	60	2 3/8	13	0,85	24	
CDF404	0 - 105	0 - 4 1/4	85	2 3/4	16.5	1,60	12	
CDF406	0 - 150	0 - 6	100	3 5/8	17	2,32	8	
CDF408	0 - 205	0 - 8	125	4 1/2	17	3,42	6	
CDF410	50-245	2 - 10	150	5 3/8	18	5,49	4	
CDF412	50-305	2 - 12	160	5 3/4	20	6,44	2	

# C-clamps



## C-clamp CDF-C



№	← a →		← b →					VB0002
	mm	"	mm	"				
CDF402C	0 - 50	0 - 2	55	2	12	0,61	36	
CDF403C	0 - 75	0 - 3	60	2 3/8	13	0,85	24	
CDF404C	0 - 105	0 - 4 1/4	85	2 3/4	16.5	1,60	12	
CDF406C	0 - 150	0 - 6	100	3 5/8	17	2,32	8	
CDF408C	0 - 205	0 - 8	125	4 1/2	17	3,42	6	
CDF410C	50-245	2 - 10	150	5 3/8	18	5,49	4	
CDF412C	50-305	2 - 12	160	5 3/4	20	6,44	2	

- Clamping force up to 20,000 N
- Drop forged, extremely stable
- The copper-plated spindle prevents welding splatter from sticking



## C-clamp M, extremely heavy duty



№	← a →		← b →					VB0002
	mm	"	mm	"				
M101	0 - 100	0 - 4	70	2 3/4	12	1,80	1	
M103	0 - 150	0 - 6	120	4 3/4	17	3,70	1	
M104	0 - 200	0 - 7 7/8	160	6 1/4	20	5,70	1	
M105	0 - 250	0 - 10	200	7 7/8	20	8,50	1	
M106	0 - 300	0 - 12	220	8 3/4	20	10,50	1	

- Clamping pressure of up to 20,000 N
- Very sturdy, cast design